



HS SERIES

HANGING SCALE





HS

FEATURES

- Heavy Duty, Compact Size Hanging Scale
- Safety Overload > 200% of Rated Capacity
- Ultimate Overload > 300% of Rated Capacity (Max. = 60 Kg)
- Extremely Low Power Consumption : 250 Non-stop Operating Hours with 4 X UM-2 (Size C) Batteries
- User Friendly Operation with:-
 - Power On Zero Tracking
 - Power Saving Function
 - Full Tare (Subtractive) Range
 - Auto Hold Function
 - Backlight Function
 - Auto Calibration
- 5 X 24 mm Wide Angle LCD Digits
- Tact-Switch Keyboard
- User Selectable Metric and Avoirdupois Weight Units

OPTIONS AVAILABLE

- External Power Adaptor
- Rear Display
- All Stainless Steel Hanging Pan Support
- Stainless Steel Pan (290mm, Max. Cap. 30kg)

SPECIFICATIONS

Model No.	Capacity	Division
HS-3000	3000g	2g
HS-7500	7500g	5g
HS-15K	15kg	0.01kg
HS-30K	30kg	0.02kg
Power source	4 x UM-2 Batteries (not included), or External Power Adaptor (not included)	
Operating Environment	0° ~ 40°C (32° ~ 104°F), Non-condensed R.H. ≤85%	
Standard Package	10 Units in One Box 295(L) x 270(W) x 350(H) mm Net/Gross Weight : 5.8/6.3kg	

* Specifications subject to change without notice



unit = mm



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Shing Road Hsin Tien City 231 Taipei Hsien Taiwan R.O.C.
Tel : +886-2-29180121 (12 Lines) Fax : +886-2-29181508 - 29183652 - 29112176-7
<http://www.uwe-scale.com.tw> e-mail: uwe@ms8.hinet.net

Oct '99 Designed by DAILY
Printed in Taiwan